QRM A PTW COMPANY

Hip Phantom V2

The Hip Phantom can be used to examine artifacts related to hip inplants. It is also designed to evaluate bmd in quantitatve Computed Tomography (qCT) of the hip/femur region.

The Hip-Phantom comprises a water-equivalent phantom body, made from CTWater[®] and two interchangeable cylindrical inserts with a specified bone mineral density of 800 (cortical bone) and 100 /200 mg (cancellous bone) hydroxyapatite (HA) per cm³ respectively.

The bone-simulating cylinders have an outer diameter of 30 mm and a wall thickness of 5 mm (cortical bone), the inner part is 20 mm in diameter (spongious bone).

There are several different inserts available with other bmd concentrations. Inserts with metal implants can be ordered on a custom-made basis.

Specifications

| Base material | CTWater [®] |
|-----------------------|----------------------|
| Phantom cross section | 360 x 160 mm |
| Phantom depth | 100 mm |

Different additional BMD inserts as well as implants are possible. Please contact us: info@qrm.de



The QRM-Hip-Phantom



Schematic drawing of the phantom.

深圳市展业达鸿科技有限公司

吕先生:15920060912(微信同号) 0755-22934005(座机) 地址:深圳市福田区八卦二路八卦岭工业区615栋419 邮箱:hongqi@thingstet.com 网址:www.thingstest.com