

Over 30 years of innovative gas analysis!

PRECISION MULTIFUNCTION MANOMETER FOR ENGINE TESTING



Gas leak detector in the inlet area



MRU DM 9600 Precision Manometer FOR ENGINE TESTING

KEY FEATURES

- >> Large 2.8" Color, touch screen
- >> AUX input for Leak detection or external pressure probes
- >> Automatic zeroing for long-term stability
- >> Two (2) K type thermocouple sockets
- >> Simultaneous display of pressure and temperature readings
- >> 1,000 points and 500 sites data memory
- >> Micro SD card slot
- >> USB charging and data download
- >> Hands free operation via magnetic back case
- >> 20-hour Lithium battery

Technical Data

1 Common Data				
Parameter	Range	Accuracy	Range	Accuracy
Engine inlet pressure	100 200 mbar	± 1 mbar or 1 % reading	40 to 80 inH2O	± 0.4 inH2O or 1 % reading
Boost pressure	1 4 bar	± 1 mbar or 1 % reading	14.5 to 58 psi	± 0.4 inH2O or 1 % reading
Intercooler differential pressure	200 500 mbar	± 1 mbar or 1 % reading	80 to 200 inH2O	± 0.4 inH2O or 1 % reading
Exhaust back pressure	20 200 mbar	± 1 mbar or 1 % reading	8 to 80 inH2O	± 0.4 inH2O or 1 % reading
Carter pressure	0 200 mbar	± 1 mbar or 1 % reading	0 to 80 inH2O	± 0.4 inH2O or 1 % reading
Internal pressure (ext. transmitter)	1 9 bar	± 20 mbar or 1 % reading	14.5 to 130 psi	± 8 inH2O or 1 % reading
Temperature	0 1,000 °C	± 1 °C or 1 % reading	32°F to 1830°F	± 2 °F or 1 % reading
Gas leackage	5 20,000 ppm	NA	5 20,000 ppm	NA
Temperature variation	0 50°C	± 0.5%	32°F to 122°F	± 0.5%

General technical data:

Measuring units	Pressure (inH2O, Pa, hPa, mbar, bar, psi, mm Hg);		
	Temp: C/F; Flow: fpm, m/s, CFM, m3/sec; HC: ppm to %LEL		
Interfaces	Mini-USB, Micro-SD, Bluetooth (option)		
Rechargeable Battery	Lithium-lon		
Dimensions	(W x H x D) 3.23" x 6.65" x 1.42" (82 x 169 x 36 mm)		
Weight	approx. 14 ounces (400g)		

Data subject to change without notice

