

OxyTrans

4-20 mA Loop Powered Two Wire Oxygen Transmitter

Two Wire Process Oxygen Transmitter

The Model OxyTrans is an easy to use, accurate and economical way to measure oxygen at trace and % levels. A simple display and one point calibration allows for a quick start of the instrument.

Edgetech Instruments' services are performed in the USA at their modern, well-staffed, ISO/IEC 17025:2017 accredited, ISO 9001:2015 registered manufacturing facility. All recertifications and calibrations are traceable to NIST.

Measuring Range:

The unit offers ranges between
0-100 ppm, 0-1,000 ppm, 0-10,000 ppm of oxygen and
0-1% to 0-25% oxygen.

Sensor:

The OxyTrans uses a special fuel cell to measure the oxygen concentration. The sensor meets the industrial requirements for accuracy, sensitivity, easy to use and operating life.

Calibration:

The calibration of the instrument for trace oxygen measurements in gas should be done with a known calibrated gas. The concentration can be chosen freely within the measuring range.

Flow-Through Measuring Cell in Stainless Steel:

The measuring cell is modular and made of stainless steel. A defective measuring cell can be repaired by replacing the defective part only, rather than the complete unit.

Features:

- Compact
- Inexpensive
- Sensor with long operating life
- IP65 enclosure
- Reverse voltage protection and temperature
- compensation

Applications:

- Semiconductor Industry
- Gas Manufacturers
- Metallurgical Industries
- Chemical Industry
- Heat Treating and Bright Annealing
- Hydrogen/Flammable Gas



The OxyTrans T-PSS



The OxyTrans T



The OxyTrans T-RA

Technical Specifications

Measuring Ranges:

- O₂ PPM Range: 0-100 ppm
- 0-1,000 ppm
- 0-10,000 ppm
- O₂ % Range: 0-1%, 0-25%
- Range must be specified at time of ordering.

Calibration:

- With calibrated gas, air

Accuracy:

- $\pm 2\%$ FSD T = constant
- $\pm 5\%$ FSD 0>T>50°C

Resolution:

- 0.1 ppm at 0-100 ppm
- 1 ppm at 0-1,000; 0-10,000 ppm
- 0.1%

Response Time:

- 90% FSD at 25°C
- 0-10 ppm < 45 s
- 0-100 ppm < 20 s
- 0-1,000 ppm < 10 s

Operating

- Temperature:
- 0 - 50°C

Pressure:

- 0.1 - 1 bar

Signal Output:

- 4 - 20 mA/dc

Alarm Value:

- 3.8 mA (Standard) or
- 23mA (Optional)

Voltage:

- 10 - 35 Vdc

Load Range:

- 100 to 750 ohm
- Typ. 470 ohm

Display:

- 6 Digits, alphanumeric with bar graph

Oxygen Sensor:

- Micro-Fuel Cell

Housing:

- IP65

Dimensions:

- 120 mm x 160 mm x 65 mm (L X H X W)
- 4.7" x 6.3" x 2.5"

Weight:

- 1.2 kg (206 lb)

Options:

- Different sensors available
- 5 different ranges
- 316 stainless steel cell BI

Model Types

OxyT	Standard
OxyT-H	Works with the Hart Protocol
OxyT-RA	Right angle display
OxyT-SS	Panel mount sampling system Panel size: 38.1 cm (15") square Weight: 3.2 kg (7 lb)
OxyT-PSS	Portable sampling system with power supply and pump option Weight: 6.8 kg (15 lbs)
OxyTrans-EX	Explosion Proof, 2 wire loop powered transmitter (ATEX approved)



The OxyTrans T-SS

